	Product Name:	ABT-HC-UCFS-0520
Description: Premier Undercounter Laboratory Freezer Freestanding (-20°C)	. roddot raino.	7.05 1.10 001 0 0020
4 Cu. Ft. Capacity One solid swing door, right hinged, not reversible Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms 2 probes; 1 in air and 1 in sample bottle Remote alarm contacts Adjustable operating temperature range: -15°C – -25°C 2 fixed shelves Bottom footed shelf to allow air circulation Back wall evaporator cover Keyed door lock Magnetic door gasket for positive seal Recessed door handle Leveling legs LED interior light Probe access port (3/8") White cabinet and door High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Two year parts and labor warranty, plus an additional three year compressor parts only warranty Exterior dimensions: 23 5/8" W x 24 1/4"D x 32 3/16"H Note: This unit must have 4" clearance on sides and back for adequate ventilation Manual defrost 115V, 60 Hz, 1.4 Amps, 1/8 HP UL/C-UL listed Shipping weight: 128 lbs.	Description:	4 Cu. Ft. Capacity One solid swing door, right hinged, not reversible Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms 2 probes; 1 in air and 1 in sample bottle Remote alarm contacts Adjustable operating temperature range: -15°C – -25°C 2 fixed shelves Bottom footed shelf to allow air circulation Back wall evaporator cover Keyed door lock Magnetic door gasket for positive seal Recessed door handle Leveling legs LED interior light Probe access port (3/8") White cabinet and door High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Two year parts and labor warranty, plus an additional three year compressor parts only warranty Exterior dimensions: 23 5/8" W x 24 1/4"D x 32 3/16"H Note: This unit must have 4" clearance on sides and back for adequate ventilation Manual defrost 115V, 60 Hz, 1.4 Amps, 1/8 HP UL/C-UL listed