Product Name:	ABT-HC-I P-36
1 10ddot 14dillo.	
Description:	Premier Glass Door Laboratory Refrigerator 36 Cu. Ft. capacity Two swing glass doors, self-closing, right hinged, not reversible Microprocessor Temperature Controller Adjustable operating temperature range: 1°-10°C Digital Temperature Display and Alarm Module Sample simulated digital temperature display; .1° Resolution Adjustable temperature display in Celsius or Fahrenheit Audible and visual high/low temperature alarms 2 probes; 1 in air and 1 in sample bottle Sensor error alarm Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Eight adjustable shelves (adjustable in ½" increments) Keyed door lock Forced draft air circulation Magnetic door gasket for positive seal Heavy duty door handle LED interior lights are safety shielded and switch controlled Swivel Casters (3 ½") Probe access port (¾") White powder-coated steel exterior and interior High density urethane foam cabinet insulation Hydrocarbon, natural refrigerant (R290) Two year parts and labor warranty, plus an additional three compressor parts warranty Exterior dimensions: 39 ¾" W x 3 4 3/4" D x 81 ¾" H with casters; 78 ¼" H without casters Cycle defrost 115V, 60 Hz, 4.5 Amps, 1/4 HP ETL listed Shipping weight: 405 lbs.
L	I