

Product Name:	PH-ABT-HC-69G
Description:	<p>Premier Pharmacy/Vaccine Sliding Glass Door Refrigerator  69 Cu. Ft. capacity  Three sliding glass doors, self-closing (energy efficient, double pane vacuum insulated)  Microprocessor Temperature Controller  Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C)  Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual &amp; audible temp alarm  Standard Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms  Sample simulated digital temperature display; .1° Resolution  Adjustable temperature display in Celsius or Fahrenheit  Audible and visual high/low temperature alarms  2 probes; 1 in air and 1 in sample bottle  Sensor error alarm  Power failure alarm  Resettable 1-point Min/Max History  Remote alarm contacts  Alarm validation (audible, visual, and remote alarm)  Alarm mute with ring back  18 total shelves, 12 adjustable plus 6 additional  Vaccine storage power cord warning label  Forced draft air circulation  Keyed door lock  Magnetic door gasket for positive seal  Integrated door handles  LED interior lights are safety shielded and switch controlled  Swivel Casters (3 ½")  Probe access port (⅜")  Powder coated steel white exterior and interior  Hydrocarbon, natural refrigerant (R290)  Pharmacy refrigerator/freezer toolkit and temperature logs  Two year parts and labor warranty, plus an additional three year compressor parts warranty  Exterior dimensions: 81" W x 33 ¼" D x 81 ¾" H with casters; 78 ¼" H without casters  Cycle defrost  115V, 60 Hz, 7.5 Amps, 1/2 HP  ETL listed  Shipping weight: 738 lbs.</p>