Description:  ABS Auto Max System Auto Fill Tank Total Vial Capacity (2 mL vials): 10,400 Total Bag Capacity: 235 LN2 Capacity (Liters): 165 Static Evaporation Rate (Liters/Day): 5 Normal working time (days): 33 Power requirement: 24 Vac Exterior Width (mm): 586.7 Overall Height (mm): 1117.6 Exterior Depth (mm): 774.7 Usable Height (mm): 736.6 Internal Diameter (mm): 533.4 Sentry Controller Controller features:  Temperature display (Celsius) Level accuracy with 4 direct read sensors Large format LED display Alarm ring back Redundant level sensor system Remote monitoring system available Liquid level indicator Alarm package (audible, visual, and remote) including level (high and low), high temperature, and sensor failure UL-Listed transformer	Product Name:	AMIV-1
Auto Fill Tank Total Vial Capacity (2 mL vials): 10,400 Total Bag Capacity: 235 LN2 Capacity (Liters): 165 Static Evaporation Rate (Liters/Day): 5 Normal working time (days): 33 Power requirement: 24 Vac Exterior Width (mm): 586.7 Overall Height (mm): 1117.6 Exterior Depth (mm): 774.7 Usable Height (mm): 533.4 Sentry Controller Controller features:  Temperature display (Celsius) Level accuracy with 4 direct read sensors Large format LED display Alarm ring back Redundant level sensor system Remote monitoring system available Liquid level indicator Alarm package (audible, visual, and remote) including level (high and low), high temperature, and sensor failure		
Stainless steel vacuum tank Recessed casters Fiberglass top Full access opening Leveling platform Stainless steel armor-plated transfer hose 7-inch foam insulated hinged lid with locking provision, protective		ABS Auto Max System Auto Fill Tank Total Vial Capacity (2 mL vials): 10,400 Total Bag Capacity: 235 LN2 Capacity (Liters): 165 Static Evaporation Rate (Liters/Day): 5 Normal working time (days): 33 Power requirement: 24 Vac Exterior Width (mm): 586.7 Overall Height (mm): 1117.6 Exterior Depth (mm): 774.7 Usable Height (mm): 533.4 Sentry Controller Controller features:  Temperature display (Celsius) Level accuracy with 4 direct read sensors Large format LED display Alarm ring back Redundant level sensor system Remote monitoring system available Liquid level indicator Alarm package (audible, visual, and remote) including level (high and low), high temperature, and sensor failure UL-Listed transformer Stainless steel vacuum tank Recessed casters Fiberglass top Full access opening Leveling platform Stainless steel armor-plated transfer hose 7-inch foam insulated hinged lid with locking provision, protective boot, and pneumatic lifters
Stainless steel vacuum tank Recessed casters Fiberglass top Full access opening Leveling platform Stainless steel armor-plated transfer hose 7-inch foam insulated hinged lid with locking provision, protective		<ul> <li>Level accuracy with 4 direct read sensors</li> <li>Large format LED display</li> <li>Alarm ring back</li> <li>Redundant level sensor system</li> <li>Remote monitoring system available</li> <li>Liquid level indicator</li> <li>Alarm package (audible, visual, and remote) including level (high and low), high temperature, and sensor failure</li> <li>UL-Listed transformer</li> <li>Stainless steel vacuum tank</li> <li>Recessed casters</li> <li>Fiberglass top</li> <li>Full access opening</li> <li>Leveling platform</li> <li>Stainless steel armor-plated transfer hose</li> <li>7-inch foam insulated hinged lid with locking provision, protective</li> </ul>
hoot and pneumatic litters		boot, and pneumatic lifters One-year warranty on all parts and labor Three-year vacuum warranty