

Product Name:	CRT-ABT-HC-UCFS-0104
Description:	<p>Undercounter Controlled Room Temperature Cabinet, Freestanding 1 Cu. Ft. Capacity One solid swing door, right hinged* Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in sample bottle Adjustable operating temperature range: 68°F–77°F (20°C – 25°C) Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm Back wall evaporator cover 2 adjustable shelves Vaccine storage power cord warning label Forced draft circulation Keyed door lock Integrated door handle Magnetic door gasket for positive seal Leveling legs LED interior light Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 17 ¼" W x 19 ¼" D x 21 ¼"H <i>Note: This unit must have 4" clearance on sides and back for adequate ventilation</i> Cycle defrost 115V, 60 Hz, .90 Amps, 1/8 HP ENERGY STAR CERTIFIED UL/C-UL listed Shipping weight: 91 lbs. *This product is available left hinged, product number CRT-ABT-HC-UCFS-0104-LH</p>