

Product Name:	CRT-ABT-HC-UCFS-0104G
Description:	<p>Undercounter Controlled Room Temperature Cabinet, Freestanding  1 Cu. Ft. Capacity  One glass swing door, right hinged*  Microprocessor temperature controller  Digital temperature display  Audible and visual high and low temperature alarms  Remote alarm contacts  2 probes; 1 in air and 1 in sample bottle  Adjustable operating temperature range: 68°F–77°F (20°C – 25°C)  Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual &amp; audible temp alarm  2 adjustable shelves  Back wall evaporator cover  Vaccine storage power cord warning label  Forced draft circulation  Keyed door lock  Integrated door handle  Magnetic door gasket for positive seal  Leveling legs  LED interior light  Probe access port (3/8")  Powder coat exterior  High density urethane foam cabinet and door insulation  HFC-free refrigerant (R600a), foam insulation and packaging  Two year parts and labor warranty, plus an additional three year compressor parts only warranty  Pyxis<sup>®</sup>, Omnicell<sup>®</sup> and AcuDose RX<sup>®</sup> compatible  Exterior dimensions: 17 ¼" W x 19 ¼" D x 21 ¼"H  <i>Note: This unit must have 4" clearance on sides and back for adequate ventilation</i>  Cycle defrost  115V, 60 Hz, .90 Amps, 1/8 HP  ENERGY STAR CERTIFIED  UL/C-UL listed  Shipping weight: 91 lbs.  *This product is available left hinged, product number CRT-ABT-HC-UCFS-0404G-LH</p>