| | |
|---|---|
| Product Name: | ABT-HC-72 |
| | |
| Description: | Premier Glass Door Laboratory Refrigerator<br>72 Cu. Ft. capacity<br>Three swing glass doors, self-closing (energy efficient, double pane vacuum insulated)<br>Microprocessor Temperature Controller<br>Adjustable operating temperature range: 1°-10°C<br>Standard Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms<br>Sample simulated digital temperature display; .1° Resolution<br>Adjustable temperature display in Celsius or Fahrenheit<br>Audible and visual high/low temperature alarms<br>Sensor error alarm<br>Power failure alarm<br>Resettable 1-point Min/Max History<br>Remote alarm contacts<br>Alarm validation (audible, visual, and remote alarm)<br>Alarm mute with ring back<br>Twelve adjustable shelves (adjustable in ½" increments)<br>Forced draft air circulation<br>Keyed door lock<br>Magnetic door gasket for positive seal<br>Heavy duty door handles<br>LED interior lights are safety shielded and switch controlled<br>Swivel casters (adds 4" to height)<br>Probe access port (3/8")<br>White laminated vinyl exterior<br>White aluminum liner and stainless steel floor interior<br>HFC-free refrigerant (R290), foam insulation and packaging<br>Two year parts and labor warranty, plus an additional three year compressor parts warranty<br>Exterior dimensions: 78 1/4" W x 31" D x 82 5/8” H with casters; 78 5/8” H without casters<br>Cycle defrost<br>115V, 60 Hz, 8.5 Amps, 1/2 HP, BTU/HR 7315<br>UL/C-UL listed<br>Shipping weight: 690 lbs. |