

Product Name:	CRT-ABT-HC-UCFS-0504G
Description:	Undercounter Controlled Room Temperature Cabinet, Freestanding 5.2 Cu. Ft. Capacity One glass swing door, right hinged, not reversible Microprocessor temperature controller Digital temperature display Adjustable operating temperature range: 68°F–77°F (20°C – 25°C) Calibrated using a NIST traceable device, certificate included Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in sample bottle Three adjustable shelves with guard rail on back to prevent product from being pushed against the back wall Bottom footed shelf to allow air circulation Back wall evaporator cover Vaccine storage power cord warning label Forced draft circulation Keyed door lock Magnetic door gasket for positive seal Leveling legs LED interior light Switch activated light Probe access port (3/8") Powder coat exterior High density urethane foam cabinet insulation HFC-free refrigerant (R600a), foam insulation and packaging Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis[®], Omnicell[®] and AcuDose RX[®] compatible Exterior dimensions: 23 3/4"W x 24" D x 32 1/8 "H <i>Note: This unit must have 4" clearance on sides and back for adequate ventilation</i> Cycle defrost 115V, 60 Hz, 1.3 Amps, 1/6 HP ENERGY STAR CERTIFIED UL/C-UL listed Shipping weight: 129 lbs.