1 Toddot Ttarric.	PH-ABT-HC:-33G
3 T V N A C S b S A A 2 S F F F A A 1 N F K N II L C F F H F T C E 1 C 1 E	Premier Pharmacy/Vaccine Sliding Glass Door Refrigerator 33 Cu. Ft. capacity Two sliding glass doors, self-closing (energy efficient, double pane vacuum insulated) Microprocessor Temperature Controller Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C) Calibrated using a NIST traceable device, certificate included Standard Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms Sample simulated digital temperature display; .1° Resolution Adjustable temperature display in Celsius or Fahrenheit Audible and visual high/low temperature alarms 2 probes; 1 in air and 1 in sample bottle Sensor error alarm Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back 12 total shelves, 8 adjustable plus 4 additional Vaccine storage power cord warning label Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Integrated door handles LED interior lights are safety shielded and switch controlled Swivel Casters (3 ½") Probe access port (%") Powder coated steel white exterior and interior Hydrocarbon, natural refrigerant (R290) Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts warranty Exterior dimensions: 39 ½" W x 33 ¼" D x 81 ¾" H with casters; 78 ¾" H without casters Cycle defrost 115V, 60 Hz, 4.5 Amps, 1/4 HP ETL listed Shipping weight: 419 lbs.