

**Product Data Sheet**

12 CF Premier Pharmacy/Vaccine Refrigerator & Freezer  
Combination with Controlled Auto Defrost Freezer w Glass  
Door

**PH-ABT-HC-RFC12GA-CAD**

**Images**



**Product Description**

Our proprietary "Controlled Auto Defrost" technology provides the convenience of an auto-defrost design while still ensuring that vaccines remain at consistent and stable temperatures below 5°F (-15°C)

Models require 4" of clearance around back and sides of the unit for proper ventilation. Improper installation will void the warranty and will lead to temperature maintenance issues, overheating and possible failure. Product requires 2 outlets

**Certifications**



**General Description and Application**

Storage capacity (cu. ft)	12 Cu. Ft. capacity (10.5 Ref./1.0 Freezer)
Door	2 exterior swing doors (glass door refrigerator/solid door freezer)
Shelves	6 adjustable refrigerator and 2 adjustable freezer
Freezer Compartments	1
Baskets	Non-applicable
Mounting	Leveling Legs and stacking kit
Interior lighting	LED interior light (Refrigerator)
Airflow management	Forced draft air circulation, refrigerator
External probe access	Two probe access ports (3/4"
Insulation	High density urethane foam cabinet insulation
Exterior materials	Steel
Access Control	Keyed door lock
General warranty	Two (2) year parts and labor warranty
Compressor Parts Warranty	Five (5) year compressor parts warranty
Warranty Disclaimer	Indoor use only, +18C to +26C (+65F to +78F), <70% RH. Specifications are subject to change Please note this unit requires 2 outlets.
Product Weight (lbs)	246
Shipping Weight (lbs)	316
Rated Amperage	2.3 Amps refrigerator, 1 Amp freezer
Power Plug/Power Cord	NEMA 5-15 Plug, conforms to UL471 requirements . Vaccine storage power cord warning label
Facility Electrical Requirement	110-120V AC: 15 A (minimum)
Agency Listing and Certification	UL-C-UL Listed

**Refrigeration System**


Refrigerant	HFC-free refrigerant (R600a)
Defrost	Controlled Auto defrost freezer / Cycle defrost refrigerator

**Controller, Configuration, Alarms and Monitoring**

Controller technology	Microprocess temperature controller
Display technology	Digital temperature display
Adjustable Temperature Range	Refrigerator: 36°F – 46°F (2°C -8°C); Freezer: 5°F – -13°F (-15°C - -25°C)
External alarm connection	Remote alarm contacts
Alarms	Audible and visual high and low temperature alarms
Other	Pyxis®, Omnicell® and AcuDose RX® compatible
Defrost	Auto defrost cycle every 6 hours: (at Set Point -11°F /-24°C) Max air temp in empty freezer: 5°F (-15°C) Max air temp in loaded freezer: 3°F (-16°C) Max sample temp in empty freezer: 0°F (-18°C) Max sample temp in loaded freezer: -4°F (-20°C)

**Dimensions**

	Width (in.)	Depth (in.)	Height (in.)	Door Swing (in.)	Total open Depth (in.)
Exterior	23.625	26	79.875	22	48
Interior	17.875 upper / 20.375 lower	7.5 upper / 17.625 lower	12.375 upper / 53.25 lower		



**Contact**

Customer Service  
 Technical Service

800-648-4041 Option 3  
 800-648-4041 Option 5, Parts Option 4

customerservice@horizonscientific.com  
 technicalservice@horizonscientific.com

Rev\_01202025