Product Data Sheet
12 CF Premier Pharmacy/Vaccine Refrigerator & Freezer Combination with Auto Defrost

PH-ABT-HC-RFC12GA

Images

Product Description

The Premier Pharmacy Dual Temp Combination units feature separate microprocessor temperature controller allowing for precise temperature control, verification and recovery. An interior fan driven, forced-draft air circulation system provides excellent temperature uniformity and recovery after door openings. REFRIGERATORS ONLY

All models are equipped with digital temperature displays for convenient monitoring. Critical samples and supplies are security backed with an extensive package of audible and visual alarms. The freezer units feature either an automatic or manual defrost operating system. For manual defrost freezers, periodic manual defrosting is required.

This model requires 4" of clearance around back and sides of the unit for proper ventilation. Improper installation will void the warranty and will lead to temperature maintenance issues, overheating and possible failure.

DISCLAIMER: Auto defrost freezers incorporate an electric heater installed on the evaporator that assist in the removal of the frost and ice. Although the heater helps speed up the frost and ice removal, it can raise the temperatures within the freezer.

Environmentally friendly, natural hydrocarbon (HC) refrigerants (not containing hydrofluorocarbons) vastly reduce global-warming potential (GWP) while meeting new EPA/SNAP mandates and UL, ASHRAE compliance guidelines.

Certifications

c UL us

General Description and Application	
Storage capacity (cu. ft)	12 Cu. Ft. capacity (10.5 Ref./1.3 Freezer)
Door	1 Glass Door Refrigerator and 1 Solid Door Freezer
Shelves	6 adjustable refrigerator and 2 adjustable freezer
Freezer Compartments	1
Baskets	Non-applicable
Mounting	Leveling Legs and stacking kit
Interior lighting	LED lights
Airflow management	Forced draft air ciculation, refrigerator
External probe access	Two probe access ports (3/4"); one, refrigerator/one, freezer
Insulation	High density urethane foam cabinet insulation
Exterior materials	Steel
Access Control	Keyed door lock
General warranty	Two (2) year parts and labor warranty
Compressor Parts Warranty	Five (5) year compressor parts warranty
Product Weight (lbs)	219
Shipping Weight (lbs)	289
Rated Amperage	2.3 Amps refrigerator, 1 Amp freezer
Power Plug/Power Cord	NEMA 5-15 Plug, conforms to UL471 requirements . Vaccine storage power cord warning label
Facility Electrical Requirement	110-120V AC: 15 A (minimum)
Agency Listing and Certification	UL-C-UL Listed

Refrigeration System	
Refrigerant	HFC-free refrigerant (R600a)
Defrost	Auto defrost freezer / Cycle defrost refrigerator

Controller, Configuration, Alarms and Monitoring	
Controller technology	Microprocess temperature controller
Display technology	Digital temperature display
Adjustable Temperature Range	Refrigerator: 36°F – 46°F (2°C -8°C); Freezer: 5°F – -13°F (-15°C - -25°C)
External alarm connection	Remote alarm contacts
Alarms	Audible and visual high and low temperature alarms
Other	Pyxis®, Omnicell® and AcuDose RX® compatible
Warranty Disclaimer	Indoor use only, +18C to +26C (+65F to +78F), <70% RH.
	Specifications are subject to change. Requires 2 outlets. Models require 4" of clearance around back and sides of the unit for proper
	ventilation. Improper installation will void the warranty and will lead to temperature maintenance issues, overheating and possible failure. Auto defrost freezers incorporate an electric heater
	installed on the evaporator that assist in the removal of the frost and ice. Although the heater helps speed up

Dimensions

	Width (in.)	Depth (in.)	Height (in.)	Door Swing (in.)	Total open Depth (in.)
Exterior	23.625"	26.5"	80.25"	22"	47.75"
Interior	17.875" upper /19.875" lower	9.125" upper /17.625" lower	13.75" upper /53.25" lower		



Contact

Customer Service	800-648-4041 Option 3	customerservice@horizonscientific.com
Technical Service	800-648-4041 Option 5, Parts Option 4	technicalservice@horizonscientific.com

Rev_01202025