Due di cet Mense.	DILART HO HODI 040400 III
Product Name:	PH-AB1-HC-UCBI-040455-LH
Product Name: Description:	LEFT-HINGED 4.6 Cu. Ft. Capacity One solid stainless steel swing door, left hinged Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in sample bottle Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C) Calibrated using a NIST traceable device, certificate included Three shelves (two adjustable/one fixed) with guard rail on back to prevent product from pushing against back wall Back wall evaporator cover Vaccine storage power cord warning label Forced draft circulation Recessed door handle Keyed door lock Magnetic door gasket for positive seal Leveling legs Probe access port (3/8") Stainless steel exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts only warranty
	Recessed door handle
	Magnetic door gasket for positive seal
	Probe access port (3/8")
	High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year
	Exterior dimensions: 23 ¾"W x 24 ½"D x 33 ¾"H Cycle defrost
	115V, 60 Hz, 1.74 Amps, 1/8 HP Energy Consumption 1.15 kWh/day UL/C-UL listed
	ENERGY STAR CERTIFIED Shipping weight: 135 lbs.