Product Name:	PH-ABT-HC-UCBI-0420A-LH
Description:	
	Built-In-LEFT HINGED 4.2 Cu. Ft. Capacity
	One solid swing door, left hinged, not reversible
	Microprocessor temperature controller
	Digital temperature display
	Audible and visual high and low temperature alarms
	2 probes; 1 in air and 1 in glycol bottle
	Adjustable operating temperature range: 5°F – -13°F (-15°C – - 25°C)
	Auto defrost cycle every 6 hours, max air temp in empty freezer:
	+4.34°C; max air temp in loaded freezer: -2.89°C. Max sample temp
	in empty freezer: -4.76°C; max sample temp in loaded freezer: -9.58°C
	Calibrated using a NIST traceable device, certificate included
	Three adjustable shelves with guard rail on back to prevent product
	from being pushed against the back wall
	Vaccine storage power cord warning label
	Back wall evaporator cover
	Keyed door lock Heavy duty door handle
	Magnetic door gasket for positive seal
	Leveling legs
	Probe access port (3/8")
	Powder coat exterior
	High density urethane foam cabinet and door insulation
	HFC-free refrigerant (R290), foam insulation and packaging
	Pharmacy refrigerator/freezer toolkit and temperature logs
	Two year parts and labor warranty, plus an additional three year
	compressor parts only warranty
	Pyxis®, Omnicell® and AcuDose RX® compatible
	Exterior dimensions: 23 3/4" W x 24 1/2" D x 33 1/8"H
	Auto Defrost
	115V, 60 Hz, 1.8 Amps 1/8 HP UL/C-UL listed
	Shipping weight: 143 lbs.
	DISCLAIMER: Auto defrost freezers incorporate an electric heater
	installed on the evaporator that assist in the removal of the frost and
	ice. Although the heater helps speed up the frost and ice removal, it
	can raise the temperatures within the freezer.