Product Name: Permier Pharmacy/Vaccine Countertop Laboratory Freezer Freestanding-LEFT HINGED 1.7 Cu. Ft. Capacity One solid swing door, left hinged, not reversible Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: 5°F – ·13°F (-15°C – · 25°C) Calibrated using a NIST traceable device, certificate included 2 adjustable shelves with guard rail to prevent product from being pushed against back wall Bottom footed shelf to allow air circulation Vaccine storage power cord warning label Keyed door lock Magnetic door gasket for positive seal Leveling legs Integrated door handle Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 ¾"W x 24"D x 20 ¾"H Note: This unit must have 4" clearance on sides and back for adequate ventilation Manual defrost 115V, 60 Hz, 1 Amp,1/8 HP Energy Consumption 0.75 kWh/day UL/C-UL listed ENERGY STAR CERTIFIED Shipping weight: 106 lbs.		
Freestanding-LEFT HINGED 1.7 Cu. Ft. Capacity One solid swing door, left hinged, not reversible Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: 5°F – -13°F (-15°C – -25°C) Calibrated using a NIST traceable device, certificate included 2 adjustable shelves with guard rail to prevent product from being pushed against back wall Bottom footed shelf to allow air circulation Vaccine storage power cord warning label Keyed door lock Magnetic door gasket for positive seal Leveling legs Integrated door handle Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 ¾"W x 24"D x 20 %"H Note: This unit must have 4" clearance on sides and back for adequate ventilation Manual defrost 115V, 60 Hz, 1 Amp,1/8 HP Energy Consumption 0.75 kWh/day UL/C-UL listed ENERGY STAR CERTIFIED	Product Name:	PH-ABT-HC-UCFS-0120-LH
Freestanding-LEFT HINGED 1.7 Cu. Ft. Capacity One solid swing door, left hinged, not reversible Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: 5°F – -13°F (-15°C – -25°C) Calibrated using a NIST traceable device, certificate included 2 adjustable shelves with guard rail to prevent product from being pushed against back wall Bottom footed shelf to allow air circulation Vaccine storage power cord warning label Keyed door lock Magnetic door gasket for positive seal Leveling legs Integrated door handle Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 ¾"W x 24"D x 20 %"H Note: This unit must have 4" clearance on sides and back for adequate ventilation Manual defrost 115V, 60 Hz, 1 Amp,1/8 HP Energy Consumption 0.75 kWh/day UL/C-UL listed ENERGY STAR CERTIFIED		
Vaccine storage power cord warning label Keyed door lock Magnetic door gasket for positive seal Leveling legs Integrated door handle Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 ¾"W x 24"D x 20 ¾"H Note: This unit must have 4" clearance on sides and back for adequate ventilation Manual defrost 115V, 60 Hz, 1 Amp,1/8 HP Energy Consumption 0.75 kWh/day UL/C-UL listed ENERGY STAR CERTIFIED		Premier Pharmacy/Vaccine Countertop Laboratory Freezer Freestanding-LEFT HINGED 1.7 Cu. Ft. Capacity One solid swing door, left hinged, not reversible Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: 5°F – -13°F (-15°C – -25°C) Calibrated using a NIST traceable device, certificate included 2 adjustable shelves with guard rail to prevent product from being pushed against back wall
Keyed door lock Magnetic door gasket for positive seal Leveling legs Integrated door handle Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 ¾"W x 24"D x 20 ¾"H Note: This unit must have 4" clearance on sides and back for adequate ventilation Manual defrost 115V, 60 Hz, 1 Amp,1/8 HP Energy Consumption 0.75 kWh/day UL/C-UL listed ENERGY STAR CERTIFIED		
Magnetic door gasket for positive seal Leveling legs Integrated door handle Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 ¾"W x 24"D x 20 ¾"H Note: This unit must have 4" clearance on sides and back for adequate ventilation Manual defrost 115V, 60 Hz, 1 Amp,1/8 HP Energy Consumption 0.75 kWh/day UL/C-UL listed ENERGY STAR CERTIFIED		
Integrated door handle Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 ¾"W x 24"D x 20 ¾"H Note: This unit must have 4" clearance on sides and back for adequate ventilation Manual defrost 115V, 60 Hz, 1 Amp,1/8 HP Energy Consumption 0.75 kWh/day UL/C-UL listed ENERGY STAR CERTIFIED		Magnetic door gasket for positive seal
Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 ¾"W x 24"D x 20 ¾"H Note: This unit must have 4" clearance on sides and back for adequate ventilation Manual defrost 115V, 60 Hz, 1 Amp,1/8 HP Energy Consumption 0.75 kWh/day UL/C-UL listed ENERGY STAR CERTIFIED		
High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 ¾"W x 24"D x 20 ¾"H Note: This unit must have 4" clearance on sides and back for adequate ventilation Manual defrost 115V, 60 Hz, 1 Amp,1/8 HP Energy Consumption 0.75 kWh/day UL/C-UL listed ENERGY STAR CERTIFIED		
HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 ¾"W x 24"D x 20 ¾"H Note: This unit must have 4" clearance on sides and back for adequate ventilation Manual defrost 115V, 60 Hz, 1 Amp,1/8 HP Energy Consumption 0.75 kWh/day UL/C-UL listed ENERGY STAR CERTIFIED		Powder coat exterior
Exterior dimensions: 23 ¾"W x 24"D x 20 ¾"H Note: This unit must have 4" clearance on sides and back for adequate ventilation Manual defrost 115V, 60 Hz, 1 Amp,1/8 HP Energy Consumption 0.75 kWh/day UL/C-UL listed ENERGY STAR CERTIFIED		HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts only warranty
adequate ventilation Manual defrost 115V, 60 Hz, 1 Amp,1/8 HP Energy Consumption 0.75 kWh/day UL/C-UL listed ENERGY STAR CERTIFIED		• · · · · · · · · · · · · · · · · · ·
115V, 60 Hz, 1 Amp,1/8 HP Energy Consumption 0.75 kWh/day UL/C-UL listed ENERGY STAR CERTIFIED		adequate ventilation
Energy Consumption 0.75 kWh/day UL/C-UL listed ENERGY STAR CERTIFIED		
ENERGY STAR CERTIFIED		Energy Consumption 0.75 kWh/day
Shipping weight: 106 lbs.		
		Shipping weight: 106 lbs.